Quick Change Screw Fitting Discs

For general use including blending welds and removing machining marks. Also suitable for use on mild contours as well as flat surfaces. Quick change screw fitting ensures that the disc is always perfectly centred without adhesive, moving parts or centre screw damage to the workpiece. Higher speeds can be attained resulting in faster stock removal reduced man-hours and increased productivity. Available in two abrasive types, aluminium oxide for general-purpose use and zirconia alumina for grinding and finishing of stainless steel. Available in 25mm, 38mm, 50mm, 75mm and 100mm diameters for the abrasive discs. Also available in a surface preparation material that is designed for smoothing surfaces prior to painting, removing rust, oxides, imperfections and blending out grit disc marks to produce fine finishes on metal. All discs are compatible with 3M ROLOCTM system holders.

| Disc Dia. | | Weight er 100 | Order Code YRK-205 | Price/100 TB |
|--------------|----------------------------|------------------------------|--------------------------------------|--|
| 25mm | P36 P40 P50 | 220g 220g 220g | -5010K -5020K -5030K | 2295.00 2295.00 2295.00 |
| | P60 P80 P100 | 220g 220g 220g | -5040K -5050K -5060K | 2295.00 2295.00 2295.00 |
| | P120 P180 P36 | 220g 220g 320g | -5070K -5080K -5110K | 2295.00 2295.00 2358.00 |
| 38mm | P40 P50 | 320g 320g | -5120K -5130K | 2358.00 2358.00 |
| | P60 P80 P100 P180 | 320g 320g 320g 320g | -5140K -5150K -5160K -5180K | 2358.00 2358.00 2358.00 2358.00 |
| 50mm | P36 P40 P50 | 620g 620g 620g | -5210K -5220K -5230K | 3536.00 4421.00 4421.00 |
| | P60 P80 P100 | 620g 620g 620g | -5240K -5250K -5260K | 4421.00 4421.00 4421.00 |
| | P120 P180 P36 | 620g 620g 1330g | -5270K -5280K -5310K | 4421.00 4421.00 5304.00 |
| 75mm | P40 P50 | 1330g 1330g | -5320K -5330K | 5304.00 5304.00 |
| | P80 P100 | 1330g 1330g 1330g | -5340K -5350K -5360K | 5304.00 5304.00 5304.00 |
| | | 1330g 1330g | -5370K -5380K | 5304.00 5304.00 |


Surface Preparation Discs

Designed for cleaning and finishing on all metals. Leaves a burr-free surface ready for painting or coating. Can also be used for the removal of light rust, oxides and coatings.



| Disc Dia. | Grit | Weight per 100 | Order Code YRK-205 | Price/100 TB |
|--------------|------|--------------------------|----------------------------|-------------------------------|
| 50mm | | 630g 630g e 630g | -6210K -6220K -6230K | 5894.00 5894.00 5894.00 |
| 75mm | Med | 1330g 1330g e1330g | -6310K -6320K -6330K | 7531.00 8385.00 9156.00 |





Quick Change Screw Fitting Disc Kits

Multi-purpose kit containing: one of each surface preparation disc fine, medium and coarse. Two of each abrasive disc grades P36, P60, P80 and P120. One 6mm diameter shank to fit the backing pad.



Surface Conditioning Kit

Aluminium oxide abrasive discs with quick change screw fitting. For cleaning and finishing on all metals leaving a burr-free surface ready for painting or coating. Can also be used for the removal of light rust, oxides and coatings. Suitable for use with power tools.

Size: 50mm diameter discs. **Contents:** 2 discs x P36, P40, P50, P60, P80, P100, P120 and P180 grade. Plus 6mm shank screw fitting disc holder.

| Size | Order Code YRK-205 | Price/1 TB | |
|------|-----------------------|---------------|--|
| 50mm | -9500K | 2723.00 | |

PIECES



Screw Fitting Disc Holders

Rubber holders to suit screw fitting discs. Supplied complete with 6mm diameter shank.

| To Suit | Weight | Order Code | Price/1 |
|-----------|--------|------------|---------|
| Disc Size | Per 25 | YRK-205 | TB |
| 25mm | 0.80kg | -6810K | 573.00 |
| 38mm | 0.95kg | -6820K | 573.00 |
| 50mm | 1.00kg | -6830K | 614.00 |
| 75mm | 2.00kg | -6840K | 739.00 |

