



SDS-Style Fitting Hammer Drill Bits

Tungsten carbide tipped and suitable for all SDS direct fitting hammer drills. High performance drill bits that withstand extreme heat generation ensuring maximum performance coupled with wear resistance. Manufactured to **DIN 8035**.



Diameter	Overall Length	Weight each	Order Code KEN-057	Price/1 TB	Diameter	Overall Length	Weight each	Order Code KEN-057	Price/1 TB
5.0mm	110.0	50g	-1000K	148.00	13.0mm	210.0	100g	-3040K	415.00
5.0mm	160.0	50g	-1020K	166.00	13.0mm	466.0	300g	-3140K	616.00
5.5mm	110.0	50g	-1200K	172.00	14.0mm	166.0	155g	-3220K	415.00
5.5mm	160.0	50g	-1220K	178.00	14.0mm	216.0	170g	-3240K	486.00
6.0mm	110.0	50g	-1400K	178.00	14.0mm	266.0	180g	-3280K	534.00
6.0mm	160.0	50g	-1420K	178.00	14.0mm	316.0	200g	-3300K	562.00
6.0mm	210.0	60g	-1440K	249.00	14.0mm	466.0	300g	-3340K	859.00
6.5mm	110.0	50g	-1600K	178.00	14.0mm	600.0	410g	-3380K	1096.00
6.5mm	160.0	50g	-1620K	178.00	15.0mm	166.0	200g	-3420K	652.00
7.0mm	110.0	60g	-1800K	190.00	15.0mm	266.0	200g	-3480K	705.00
7.0mm	160.0	70g	-1820K	213.00	15.0mm	450.0	250g	-3540K	941.00
8.0mm	110.0	80g	-2000K	213.00	16.0mm	250.0	150g	-3640K	534.00
8.0mm	160.0	80g	-2020K	213.00	16.0mm	300.0	200g	-3700K	652.00
8.0mm	210.0	90g	-2040K	213.00	16.0mm	450.0	350g	-3740K	670.00
8.0mm	260.0	110g	-2080K	261.00	16.0mm	600.0	450g	-3760K	883.00
8.0mm	400.0	180g	-2120K	366.00	17.0mm	200.0	160g	-3840K	723.00
9.0mm	210.0	100g	-2240K	273.00	18.0mm	250.0	240g	-4040K	859.00
10.0mm	110.0	70g	-2400K	226.00	18.0mm	450.0	400g	-4140K	1078.00
10.0mm	160.0	90g	-2420K	226.00	19.0mm	200.0	200g	-4240K	770.00
10.0mm	210.0	110g	-2440K	273.00	20.0mm	200.0	200g	-4440K	913.00
10.0mm	260.0	150g	-2480K	284.00	20.0mm	300.0	300g	-4500K	1161.00
10.0mm	360.0	180g	-2520K	534.00	20.0mm	450.0	480g	-4540K	1327.00
10.0mm	460.0	280g	-2540K	592.00	22.0mm	250.0	350g	-4680K	1327.00
11.0mm	160.0	110g	-2620K	249.00	22.0mm	450.0	720g	-4740K	1576.00
11.0mm	300.0	130g	-2680K	551.00	24.0mm	250.0	390g	-4880K	1492.00
12.0mm	166.0	100g	-2820K	325.00	24.0mm	450.0	770g	-4940K	1576.00
12.0mm	216.0	130g	-2840K	368.00	25.0mm	250.0	430g	-5080K	1492.00
12.0mm	316.0	170g	-2900K	486.00	25.0mm	450.0	770g	-5140K	1658.00
12.0mm	466.0	240g	-2940K	504.00	26.0mm	250.0	430g	-5280K	1492.00
12.0mm	600.0	350g	-2980K	924.00	26.0mm	450.0	850g	-5340K	1824.00
13.0mm	166.0	110g	-3020K	368.00					

SDS-Style Fitting Drill Bit Sets

Tungsten carbide tipped and suitable for all SDS direct fitting hammer drills. High performance drill bits that withstand extreme heat generation ensuring maximum performance coupled with wear resistance. Manufactured to **DIN 8035**

7 Piece

5, 6 and 8mm x 110mm overall length.

6, 8, 10 and 12mm x 160mm overall length.

9 Piece

5, 5.5, 6 and 7mm x 160mm overall length.

8 x 210mm, 8 x 260mm, 12 x 216mm,

12 x 316mm and 16 x 250mm overall length.



**9
PIECES**

Number of Pieces	Order Code KEN-057	Price/1 TB
7	-7000K	499.00
9	-7020K	999.00

KOBE Diamond Core Drill Kit

Diamond laser welded core drills are a dry cutting, high performance diamond Core Drill. For use with arbor and guide rod (hex shank or SDS Plus) plus extension, if required.

Manufactured from tool grade steel for perfect concentricity. Can be used across a wide range of building materials such as: facing bricks, concrete blocks, breeze blocks, building blocks, hand made bricks and soft to medium hard natural stones. Mounting thread is R¹/₂". Best results are achieved using an 850 watt (or higher) rotary drill with up to 300rpm, variable speed control and a slipping clutch for overload protection.



**12
PIECES**

No. of Pieces	Core Drill Sizes (mm)	Order Code KBE-280	Offer Price/1
12	42, 52, 65, 117, 127	-0300K	7344.00

Individual Diamond Core Drills

Effective Length (mm)	Cutting Dia. (mm)	Order Code KBE-280	Offer Price/1
150	42	-0310K	1173.00
	52	-0312K	1377.00
	65	-0314K	1479.00
	117	-0316K	1836.00
	127	-0318K	2091.00