**700**WATT

3774.00

700W motor. Aluminium alloy gear housing. Slim low profile body design for easy use and access. Multi-position side handle. Disc guard can be turned 60°.

Spindle locking device. Disc not included. No load speed: 11,500rpm.

Rated voltage: 240V. Spindle thread: M10 Frequency: 50Hz. Disc size: 100mm (not included).

Model

Number

**KAG 100** 



**KBE-279** 

-1420D

| Professional | Heat | Gun | Kit | with | LCD | Display |
|--------------|------|-----|-----|------|-----|---------|
| HAG200-D     |      |     |     |      |     |         |

Voltage

240V

Adjustable temperature between 60 - 600°C. Three stage airflow switch and digital LCD temperature adjuster. Stainless steel nozzle outlet and detachable heat protection sleeve allows for access into narrow areas. Overheating protection. Can be used free standing on a work surface facing upwards for handsfree use. Air inlet with lattice guard to keep out foreign matter.

Power input: 2,000W. Voltage: 230V ~ 50Hz. **Settings:** 

Stage I 350I/min 60°C, Stage II 350I/min 60°C - 600°C, Stage III 550I/min 60°C - 600°C with 2m cable and 3 pin plug.

Accessories: includes four detachable nozzles paint scraper, in a tough blow moulded case.

Weight: 2.2kg.

1001

POWER

Ø

ABRASIVES



| Voltage | Order Code<br>KBE-279 | Price/1<br>TB |
|---------|-----------------------|---------------|
| 240V    | -2140K                | 2345.00       |
|         |                       |               |

# Spare nozzles for HAG200-D:

| Nozzle<br>Type | Order Code<br>KBE-280 | Price/1<br>TB |
|----------------|-----------------------|---------------|
| Reduction      | -3400K                | 56.00         |
| Reflector      | -3410K                | 56.00         |

-3430K

-3440K

Surface

Window

# Triangular Paint Scraper

For flat and fine complex shapes.

|                          | The same of the sa |               |  |
|--------------------------|--|---------------|--|
| Description              | Order Code<br>KBE-280  | Price/1<br>TB |  |
| Triangular Paint Scraper | -3420K   | 56.00         |  |

### 22mm SDS-Plus Hammer Drill **EDH620**

Incorporating the most advanced features available, it is designed for the professional who demands speed and reliability from a rotary hammer drill, allowing you to do more in less time. Two modes of operation, rotary only and hammer drilling.

The lock-on speed button allows for continuous operation, reducing end-user fatigue. The soft ergonomic contoured pistol

grip handle helps to absorb vibration and provides a comfortable and secure grip.

No load speed: 1,050rpm. Impact rate:

4,400bpm.

Impact energy: 2.2J. Capacities: steel 13mm, concrete 3.4 - 22mm, wood 32mm.

Accessories: depth stop.

Weight: 2.50kg.



| Model  | Voltage | Order Code | Price/1  |
|--------|---------|------------|----------|
| Numbei |         | KBE-279    | TB       |
| EDH620 | 110V    | -0500K     | 11577.00 |
|        | 240V    | -0520K     | 11679.00 |

## **Orbital Palm Sander**

### **ESP110**

Dual material soft grip for operator comfort. Low vibration design with a high dust extraction rate. Fitted with a punch plate for creating dust extraction holes in abrasive sheets.

Power input: 200W. Orbits per minute:

14,000/min. Pad size: 110 x 100mm.

**Orbit diameter:** 

**Overall length:** 

137mm.



| Model  | Voltage      | Weight | Order Code       | Price/1            |
|--------|--------------|--------|------------------|--------------------|
| Number |              | each   | KBE-279          | TB                 |
| ESP110 | 110V<br>240V | 1.10kg | -2000K<br>-2020K | 6248.00<br>6248.00 |

### **Sanding Sheets**

| Model<br>Number | Туре     | Order Code<br>KBE-280 | Price/10<br>TB |
|-----------------|----------|-----------------------|----------------|
| 753052          | 60 Grit  | -3200K                | 625.00         |
| 753054          | 100 Grit | -3210K                | 625.00         |
| 753056          | 150 Grit | -3220K                | 625.00         |

# **OSAKI**

### Submersible **Water Pump**

Suitable for the effective drainage of cellars, cisterns and the general transfer of water. Can handle

solids up to 5mm diameter. Easy to remove filters for cleaning and access to the impeller. Automatic float switch. Strong double insulated case. Multi-hose adaptor-accepts

25 or 32mm outlet hoses. Overload protection. Motor: 400W (230V - 50Hz).

Max. flow rate: 7,500ltr/hr. Max. delivery height/ submersible depth: 5m.

| Model   | Order Code | Price/1 |
|---------|------------|---------|
| Number  | OSA-279    | TB      |
| WPS 400 | -0560K     | 2397.00 |



400 WATT

230V

56.00

56.00

### Submersible **Water Pump**

Suitable for the effective draining of cellars, cisterns and the general transfer of water. Capable of continuous and reliable

running, strong double insulated case with no metal parts are in contact with the water. Overload protection and easy to remove filters for cleaning and access to the impeller. Fitted with an automatic float switch and a multi hose adaptor (25, 32, 38mm), can handle solids up to 5mm diameter.

Motor: 750W.

Maximum delivery height: 8.5m.

Power cable: 10m. Flow Rate: 230ltr.

| Model   | Order Code | Price/1 |
|---------|------------|---------|
| Number  | KBE-279    | TB      |
| WPS 750 | -4470K     | 3365.00 |



620

200

110 x







