18V 2-Speed Cordless Combi Drill

Lightweight and well-balanced with a soft grip design, this drill has a built in LED light, 13mm keyless chuck, hammer-drill/ drill-driver mode selection collar and 20 stage torque adjustment collar. The variable speed with electric brake and reversible control switch gives it maximum versatility in driver mode.

No load speed: 0 - 400/0 - 1400rpm. Max torque: 35Nm. Blows per minute: 21,000bpm.

Drilling capacity: mild steel 13mm, softwood 28mm,

concrete 13mm.

Batteries: 2x 1.5Ah, 18V DC.

Model Weight Order Code Price/1 Item KBE	280 TB
Number each KBE-279 TB 18V Li-lon -579	OK 4641.00
DDH180 4.05kg - <b>0090K 13821.00</b> 18V Charger - <b>584</b>	



Item	Order Code KBE-280	Price/1 TB
18V Li-Ion	-5790K	4641.00
18V Charger	-5840M	2601.00



**18V** 







## Variable Speed Impact Driver

Soft grip design. Quick release. Integral battery level indicator. Heavy duty motor and gearbox. High impact speed.

No load speed: 0 - 2,300. Rated impact rate: 0 - 3,000bpm. Maximum torque (kg-fcm): 1,300. Screwing capacity:

Mechanical screws: M4 - M8. Standard screws: M5 - M12. High tension screws: M5 - M10. Batteries: 2x 1.3Ah NiMH.

Charge time: 1hr.

1001

POWER

0

BRASIVES



**Spare Battery & Charger** 

Model		Order Code	Price/1	Item	Order Code KBE-280	Price/1 TB
Number	each	KBE-279	TB	14.4V. 1.3Ah NiMH	-2024W	2805.00
AID14.4	1.60kg	-0600K	9767.00	230V Charger	-5903A	1529.00

This quality industrial tool is lightweight and well balanced. Soft grip design, 1/2" square final











Model	Weight	Order Code	Price/1	-
Number	each	KBE-279	TB	
AID14.4	1.60kg	-0600K	9767.00	_

**Variable Speed Cordless Impact Wrench** 

drive. Forward/reverse. Integral battery level indicator. Heavy duty motor and gearbox and variable speed trigger,













# Charge time: 1hr.

high impact speed.

## 1/2" SQUARE

No load speed: 0 - 2,300rpm. Maximum torque: 1,300kg-fcm. Impacts per minute: 0 - 3,000ipm. Batteries: 2x 1.3Ah NiMH.

- FUN FUWE	IN SUCKEIS	•	
Model Number		Order Code KBE-279	Price/1 TB
AIW14.4V	1.75kg	-0660K	10047.00



Price/1 TB Order Code **KBE-280** -2024W 14.4V, 1.3Ah NiMH 2805.00 230V Charger -5903A 1529.00

## **Impact Driver**

Compact and lightweight design allows you to get into tight spaces. Powered by a high capacity lithium-ion batteries. Rubber grip. Impact drive. Quick release 1/4" hexagon chuck. Forward and reverse. LED work light.

5228.00

#### Complete with:

Carrying case. Charger. 4x hexagon screwdriver bits. 1x 1/4" hexagon to 3/8" square drive adaptor. 5x hexagon shank drill bits.



-4020K

0.80kg







AIL7.2LI

#### MPTK130FK

Cushion grip body. Six position speed dial. Spindle lock button. Fitted with a quick change collet nut system. Ideal for a wide range of smaller DIY and craft jobs as an alternative to larger power tools Supplied in a fitted aluminium case.



Model	No Load	Power	Weight	Order Code	Price/1
Number	Speed (rpm)	Input	each	KBE-279	TB
MPT130EK	8,000 - 30,000	130W	640g	-2200K	4487.00

NEW

#### Accessories included: Flexible rubber drive shaft:

For use where maximum flexibility is required, to improve access in confined spaces. Bench clamp and tool steady.

118 Piece Accessory Kit Includes: various collets, cutters, drills, abrasives, brushes, burrs, wheels, discs and mandrels.

**Bench Clamp & Tool Steady:** 

To fix tool steady to a work bench or table to hold the multi tool in place when using the flexible drive shaft.

Description	Order Code KBE-280	Price/1 TB
Flexible Drive	-4800K	561.00
Tool Stand	-4810K	407.00

### Multi Tool Accessories

Suitable for use with KOBE, DREMEL and OSAKI Multi Tools.

Ground flute, for drilling most materials. Use with 3.2mm ( $^{1/8}$ ") 3 jaw collet.

1		
Diameter x Length	Order Code KBE-280	Price/1 TB
3.2 x 50mm	-3230K	46.00

#### **Diamond Coated Burrs**

Use with 3.2mm (1/8") 3 jaw collet.

Style &	Order Code	Price/1
Diameter (mm)	KBE-280	TB
Cylindrical 10.0	-3232K	66.00
Ball 2.4	-3234K	66.00

### Flat Cut-off Wheels


Supplied in packs of 20.



Diameter (mm)	Order Code KBE-280	Price/Pk TB
	Reinforced	
32	-3237K	77.00
	Non-reinforced	
24	-3238K	46.00
32	-3239K	66.00

### Wire Brushes

For the removal of paint, rust and burrs.



Mandrel	-		
Product Number	Shank Dia.(mm)	Order Code KBE-280	Price/1 TB
M2	3.2	-3370K	36.00

### Replacement 3 Jaw Collets

Suits Kobe and Osaki Multi Tools

ounce mode unit	. Oodin Maid 10	
For Shank	Order Code	Price/1
Size (mm)	KBE-280	TB
1.6	-3361K	26.00
2.4	-3362K	36.00
3.2	-3364K	46.00

### **Collet Nut Wrench**

Suits Kobe and Osaki Multi Tools

000		
AF Size	Order Code <b>KBE-280</b>	Price/1 TB
10mm	-3366K	26.00

#### **Mounted Points and Wheels**

3mm shank. W' numbers are for Wheels (for flat surface grinding). B' numbers are for points (Shaped for contour grinding).

	Shape Number	Diameter x Length	Order Code KBE-280	Price/1 TB
,	B52	10 x 18	-3253K	26.00
	W193	16 x 10	-3256K	20.00

#### Pink Al-ox

For use on harder metals where greater precision is required (lower stock removal rate).

Shape Number	Diameter x Length	Order Code KBE-280	Price/1 TB
B44	6.5 x 10.5	-3262K	20.00
B54	6.35 x 13.5	-3265K	16.00
B83	10 x 6.5	-3268K	16.00
B1222	9.8 x 9.8	-3271K	26.00
W164	6.35 x 14	-3274K	18.00
W173	10 x 3.2	-3277K	18.00
W193	16 x 10	-3280K	20.00

#### **Grey Silicon Carbide**

Use on stone, glass, ceramics and non-ferrous metals.

Shape Number	Diameter x Length	Order Code KBE-280	Price/1 TB
B53	8 x 15	-3283K	21.00
B121	12 x 12	-3286K	20.00

### **Green Silicon Carbide**

For applications requiring a harder abrasive price/1ing greater precision and durability (lower stock removal rate).

Shape Number	Diameter x Length	Order Code KBE-280	Price/1 TB
W164	6 x 12	-3292K	18.00
W173	10.5 x 3	-3301K	18.00
W181	13 v 1 5	-3280K	21 00

### **Grinding Wheels**

Silicon carbide: for use on stone, ceramics and non-ferrous metals.

Pink Al-ox: high hardness, use on metals. White Al-ox: free cutting, use on metals.

Diameter	Diameter	Order Code	Price/1
(mm)	x Length	KBE-280	TB
20	Silicon Carb. Pink Al-ox White Al-ox	-3244K -3247K -3250K	46.00 46.00 46.00

#### **Sharpening Stone**

Green silicon carbide: for use on non-ferrous metals and alloys.

Size	Order Code	Price/1
(mm)	KBE-280	TB
10 x 10 x 20	-3310K	26.00

### **Polishing Wheel**

Impregnated with silicon carbide. Use with spindle shown below



#### **Felt Polishing Bobs** For use with polishing

compounds to produce a high finish. Use with spindle shown below.

Shape	Diameter x Length	Order Code KBE-280	Price/1 TB
Cone	10 x 20	-3321K	26.00
Wheel	12.5 x 6	-3322K	36.00
Wheel	25 x 6.5	-3323K	46.00

#### **Spindle** To suit above, taper screw.

Product Shank Price/1 Dia.(mm) **KBE-280** Number 36.00 M1 3.2 -3371K

### Wet & Dry Discs

For use on paints, lacquers and fillers. 800 grit for fine polishing.

#### Supplied in packs of 20.

Diameter	Order Code	Price/Pk
(mm)	KBE-280	TB
20	-3341K	281.00

### **Sanding Bands**

Al-ox abrasive for shaping and smoothing wood and fibreglass and removing rust. Quick change, use with holders

shown below.

### Supplied in packs of 10.

		***	The second second
Diameter	Grit	Order Code	Price/Pk
x Length	Size	KBE-280	TB
10 x 12.5	P60	-3345K	153.00
	P120	-3347K	153.00
12.5 x 12.5	P60	-3349K	179.00
	P120	-3351K	179.00

#### **Holders**



Diameter	Shank	Order Code	Price/1
x Length	Size	KBE-280	TB
10 x 12.5	3	-3359K	128.00
12.5 x 12.5	3	-3360K	138.00


Page **243** 

## **279** INDUSTRIAL POWER TOOLS/WATER PUMPS

## B Angle Grinder - 240V

700W motor. Aluminium alloy gear housing. Slim low profile body design for easy use and access. Multi-position side handle. Disc guard can be turned 60°. Spindle locking device.

Disc not included. No load speed: 11,500rpm. Rated voltage: 240V. Spindle thread: M10





	Model Number	Voltage	Order Code <b>KBE-279</b>	Price/1 TB
_	KAG 100	240V	-1420D	3774.00

### Professional Heat Gun Kit with LCD Display **HAG200-D**

Adjustable temperature between 60 - 600°C. Three stage airflow switch and digital LCD temperature adjuster. Stainless steel nozzle outlet and detachable heat protection sleeve allows for access into narrow areas. Overheating protection. Can be used free standing on a work surface facing upwards for handsfree use. Air inlet with lattice guard to keep out foreign matter.

Power input: 2,000W. Voltage: 230V ~ 50Hz. **Settings:** 

Stage I 350I/min 60°C, Stage II 350I/min 60°C - 600°C, Stage III 550I/min 60°C - 600°C with 2m cable and 3 pin plug.

Accessories: includes four detachable nozzles paint scraper, in a tough blow moulded case.

Weight: 2.2kg.

1001

POWER

Ø

ABRASIVES



Voltage	Order Code KBE-279	
240V	-2140K	2345.00



Share 11077	ICS IUI HAUZ	UU-D.
Nozzlo	Order Code	Drice

Nozzle	Order Code	Price/1
Type	KBE-280	TB
Reduction	-3400K	56.00
Reflector	-3410K	56.00
Surface	-3430K	56.00
Window	-3440K	56.00

## Triangular Paint Scraper

For flat and fine complex shapes.

Description	Order Code KBE-280	Price/1 TB
Triangular Paint Scraper	-3420K	56.00



400 WATT

230V

## Submersible **Water Pump**

#### **WPS 400**

Suitable for the effective drainage of cellars, cisterns and the general transfer of water. Can handle

solids up to 5mm diameter. Easy to remove filters for cleaning and access to the impeller. Automatic float switch. Strong double insulated case. Multi-hose adaptor-accepts

25 or 32mm outlet hoses. Overload protection. Motor: 400W (230V - 50Hz).

**OSAKI** 

Max. flow rate: 7,500ltr/hr. Max. delivery height/ submersible depth: 5m.

Model	Order Code	Price/1
Number	OSA-279	TB
WPS 400	-0560K	2397.00

## 22mm SDS-Plus Hammer Drill

#### **EDH620**

**700**WATT

Incorporating the most advanced features available, it is designed for the professional who demands speed and reliability from a rotary hammer drill, allowing you to do more in less time. Two modes of operation, rotary only and hammer drilling.

The lock-on speed button allows for continuous operation, reducing end-user fatigue. The soft ergonomic contoured pistol

grip handle helps to absorb vibration and provides a comfortable and secure grip.

No load speed: 1,050rpm. Impact rate:

4,400bpm. Impact energy: 2.2J. Capacities: steel 13mm, concrete 3.4 - 22mm,

wood 32mm. Accessories: depth stop.

Weight: 2.50kg.



Model	Voltage	Order Code	Price/1
Number		KBE-279	TB
EDH620	110V	-0500K	11577.00
	240V	-0520K	11679.00

## **Orbital Palm Sander**

#### **ESP110**

Dual material soft grip for operator comfort. Low vibration design with a high dust extraction rate. Fitted with a punch plate for creating dust extraction holes in abrasive sheets.

Supplied with sanding paper, dust bag, punch plate.

Power input: 200W. Orbits per minute: 14,000/min.

Pad size: 110 x 100mm. **Orbit diameter:** 

**Overall length:** 

137mm.



Model	Voltage	Weight	Order Code	Price/1
Number		each	KBE-279	TB
ESP110	110V 240V	1.10kg	-2000K -2020K	6248.00 6248.00

#### **Sanding Sheets**

Model Number	Type	Order Code KBE-280	Price/10 TB
753052	60 Grit	-3200K	625.00
753054	100 Grit	-3210K	625.00
753056	150 Grit	-3220K	625.00

### Submersible **Water Pump**

Suitable for the effective draining of cellars, cisterns and the general transfer of water. Capable of continuous and reliable

running, strong double insulated case with no metal parts are in contact with the water. Overload protection and easy to remove filters for cleaning and access to the impeller. Fitted with an automatic float switch and a multi hose adaptor (25, 32, 38mm),

can handle solids up to 5mm diameter. Motor: 750W.

Maximum delivery height: 8.5m. Power cable: 10m.

Flow Rate: 230ltr.

Model	Order Code	Price/1
Number	KBE-279	TB
WPS 750	-4470K	3365.00





620

200

110 x







## **INDUSTRIAL POWER TOOLS**

**ABRASIVES** 

& POWER TOOLS

Industrial quality, for the professional user. Adjustable tool rest and spark deflector. Maintenance-free motor. Eye shield. Smooth and quiet operation. **CE** approved.

150mm Voltage: 240V. Speed: 2,800rpm.

Maximum grinding wheel width: 25mm.

Spindle diameter: 15mm.



Motor	Grinding	Weight	Order Code	Price/1
	Wheel Dia	each	KBE-261	TB
240V, 385W, 50Hz	150mm/6"	11.0kg	-1060K	6681.00

### 'Combi-Sand' Belt & Disc Sander - 370W

Light enough to be semi-portable, yet its robust construction makes it ideal for workshop use. It has a disc sanding table suitable for finish sanding and curve sanding. The disc table also tilts to 45° for bevel sanding and when used with the mitring guide is ideal for sanding compound angles.

The sanding belt is ideal for flat surface sanding but tilts up to 90° for end sanding. Can be directly connected to dust extraction (highly

recommended) by way of the 61mm outlet port on the end of the sander.

Power input: 370W.

Sanding disc: 150mm PSA (Stikit). Sanding belt: 100 x 914mm (4" x 36").

Weight: 17kg.



370 WATT



Order Code KBE-271 Price/1 TB Net Description Weight SBD370 -4140K 9690.00 17kg

200mm Voltage: 240V. **Speed:** 2,800rpm.

Maximum grinding wheel width: 25mm.

Spindle diameter: 15mm.





Motor	Grinding Wheel Dia	Weight each	Order Code KBE-261	Price/1 TB
240V, 385W, 50Hz	200mm/8"	21.2kg	-1080K	8670.00

### **Pedestal & Wall Mounted Bench Grinder Stands**

Four point fixing suitable for securely fixing bench grinders to the wall or floor. Manufactured from heavy gauge steel, all welded construction painted finish. Each mounting plate can accommodate various sizes of grinder base.

