

GROUP 331 DIGITAL INDICATORS

KENNEDY Digital Electronic External Micrometer

Features one touch preset, lightweight design, LCD display, inch/metric conversion at the touch of a button, origin setting and error alarm, ratchet thimble type adjustment and carbide tipped measuring faces. IP65 coolant proof. Supplied in fitted bench case.

Power supply: 1x SR44 battery, Order Code **EDI-904-400K** supplied.
Accuracy: ±0.001mm/0.00005".
Measuring force: 5 - 10N.
Flatness: 0.3µm.
Parallelism: 1µm.
Resolution: 0.001mm/0.00005".



IP65

Coolant Proof



No Data Output

Range	Weight each	Order Code	Price/1 TB
0 - 25mm/0 - 1"	270g	KEN-331	12077.00

OXFORD PRECISION External Digital Micrometer

External Digital Micrometer 0-25mm/0-1"

Oxford external digital micrometer with large digital display, quick response speed and zero set at any point. Metric/inch measurement. Can be connected to a PC serial port via the SPC cable (supplied separately). **IP65** rating.

- Easy handling
- mm/Inch measurements
- Ball end cap for measuring curved surfaces
- Large digital display
- Quick response speed
- Zero set at any point
- **IP65** rating



NEW



Range	Order Code	Price/1 TB
0 - 25mm/0 - 1"	OXD-331	3570.00

Digital Electronic External Micrometer

Easy handling with a large digital display, quick response speed and zero set at any point. Metric/inch measurement. The micrometer can be connected to a PC serial port by the SPC cable provided. **IP54** rating.

Range: 0 - 25mm/0 - 1".
Resolution: 0.001mm/0.00005".
Measuring force: 5 - 10N.
Accuracy: -0.004mm.

IP54

Protected against dust ingress and fluid splash



With SPC Data Output

Range	Resolution	Order Code	Price/1 TB
0 - 25mm/0 - 1"	0.001mm/0.0005"	-5010K	7502.00

OXFORD PRECISION IDM Digital Indicator

Features: Easy to use with clear digital LCD display. Large, easy-read 7.5mm LCD display. Soft-key touch for operator comfort, superior construction quality.
Response speed: ≤0.5m/s.
 Auto power off.



Type IDM
 Inch/metric conversion, zero reset, data hold, min. max display, fast display, auto power off.



inch mm CONVERTIBLE
TRAVEL 12.7mm 0.5"
ZERO RESET
READING 0.001mm .00005"
IP54
Protected against dust ingress and fluid splash

Description	Order Code	Price/1 TB
IDM Digital Indicator	-6020K	8267.00

IDS Digital Indicator

Features: Easy to use with clear digital LCD display. Large, easy-read 7.5mm LCD display. Soft-key touch for operator comfort. Superior construction quality.

Response speed: ≤0.5m/s.
 Auto power off.



inch mm CONVERTIBLE
TRAVEL 12.7mm 0.5"
ZERO RESET
READING 0.01mm .0005"
IP54
Protected against dust ingress and fluid splash

Description	Order Code	Price/1 TB
IDS Digital Indicator	-6010K	4187.00

KENNEDY Digital Protractor

PDV360

This digital protractor has a range of 360° split into 4 x 90° quadrants. It is simple to calibrate and the intelligent display changes orientation at 90° and 270° to remain readable. It has a 'V' groove on the top and bottom for easy placement on acute angled or cylindrical objects. 3V lithium battery gives up to 2000 hours use. Complete with a leatherette pouch that has a belt loop.



Resolution: 0.1°



Range	Weight each	Order Code	Price/1 TB
360° (90° x 4)	10.2kg	-4020K	2703.00

PRECISION EQUIPMENT