Direct reading external micrometer for quick and easy reading. With enamelled frame and tungsten carbide precision ground micro finish measuring faces.

Measuring range: 0 - 25mm. Graduation: 0.01mm, 0.5mm screw pitch with lock.

> Supplied in a robust case with setting key, with fitted heat shield on frame.



# 30° Anvil Micrometers

Used for measuring within small grooves or recesses and for quick comparisons of thread accuracy in screw cutting operations. With knurled thimble, ratchet stop and thumb lock. Enamelled frame with satin chromed finish barrel and sleeve.





Range	Graduation	Weight each	Order Code OXD-335	Price/1 TB
0 - 25mm	0.01mm	250g	-3520K	2147.00

## Wire Micrometer

Specially designed for measuring wire diameters 0 - 10mm. The front of the body is flat to help support the wire when measuring. With knurled thimble, ratchet stop and vernier scale barrel, all over satin chrome finish.



Capacity	Graduation	Weight each	Order Code OXD-335	Price/1 TB
0 - 10mm	0.002mm	150g	-2000K	2300.00

#### Micrometer Head

**Spherical Face** 



Spindle diameter: 5mm.

Spindle housing diameter: 9.5mm. Main body diameter: 14mm.

Accuracy: 0.004mm. Range: 0 - 13mm. Graduation: 0.01mm.

**PRECISION** 



Range	Graduation	Order Code OXD-335	Price/1 TB
) - 13mm	0.01mm	-8200K	1433.00

## **Precision Hand Tools**

Manufactured from hardened steel that has been precisely ground to produce parallel edges so that the square has an exact right angle on both the inside and outside of the stock and blade, to ensure accuracy.



Size	Tolerance	Order Code OXD-340	Price/1
(mm)	(mm)		TB
75 ( 3")	+/- 0.016	-0030K	1122.00
100 ( 4")		-0040K	1413.00
150 ( 6")		-0060K	1484.00
225 ( 9")		-0090K	2351.00
300 (12")	+/- 0.024	-0120K	3014.00

# Screw Plug Gauges

**Double-Ended** Go & No Go

do & No do		S Ban	To be the second
Thread Size	Weight each	Order Code KEN-360	Price/1 TB
Metric Co	arse – C	lass 6H To	olerance
M2.0 x 0.40	4g	-0810K	7500.00
M2.5 x 0.45	4g	-0830K	8500.00
M3.0 x 0.50	4g	-0840K	
M4.0 x 0.70	10g	-0860K	
M5.0 x 0.80	12g	-0880K	
M6.0 x 1.00	14g	-0890K	
M7.0 x 1.00	26g	-0900K	
M8.0 x 1.25	28g	-0910K	
M9.0 x 1.25	28g	-0920K	
M10.0 x 1.50	52g	-0930K	5100.00
M12.0 x 1.75	70g	-0950K	5916.00
M14.0 x 2.00	108g	-0960K	
M16.0 x 2.00	128g	-0970K	
M18.0 x 2.50	132g	-0980K	
M20.0 x 2.50	148g	-0990K	9180.00
M24.0 x 3.00	272g		
M30.0 x 3.50	484g		14280.00
M36.0 x 4.00	622g	-1050K	14535.00