Chrome vanadium steel blades with magnetic tips. Fitted with a unique dual grip triangular handle which has been designed for improved user comfort,



allowing more torque to be applied. With convenient hanging hole in the handle for storage.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 screwdriver would be suitable for most applications. DIN ISO 8764.

				(4)
Price/1 TB	Order Code KEN-572	Weight each	Blade Length	Tip Size
169.00	-5110K	25g	75mm	No.0
170.00	-5120K	55g	75mm	No.1
218.00	-4490K	80g	250mm	No.1
160.00	-5180K	40g	Stubby	No.2
177.00	-5140K	85g	100mm	No.2
218.00	-4500K	120g	250mm	No.2
284.00	-5150K	145g	150mm	No.3

210g

-5160K

331.00

200mm Flared Tip, Round Blade

No.4

To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. **DIN ISO 2380.**



HAND TOOLS

Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
3.2mm	75mm	25g	-5425K	123.00
6.5mm	Stubby	40g	-5420K	160.00
6.5mm	100mm	85g	-5430K	212.00
6.5mm	150mm	100g	-5440K	225.00
8.0mm	200mm	170g	-5450K	315.00
10.0mm	250mm	240g	-5460K	406.00

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. **DIN ISO 8764.**

~ -				
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.2	Stubby	45g	-5280K	144.00
No.0	75mm	25g	-5290K	123.00
No.1	75mm	55g	-5300K	173.00
No.1	250mm	80g	-5360K	240.00
No.2	100mm	85g	-5310K	212.00
No.2	250mm	120g	-5370K	250.00
No.3	150mm	145g	-5320K	290.00
No.4	200mm	210g	-5340K	376.00

Flared Tip, Square Blade

Square bladed screwdrivers can be gripped in a spanner or locking wrench to allow greater torque to be applied from the side rather than from directly above the screwdriver. **DIN ISO 2380.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	100mm	90g	-5500K	171.00
6.5mm	150mm	105g	-55 1 0K	180.00
8.0mm	200mm	185g	-5520K	237.00
10.0mm	250mm	275g	-5530K	329.00
10.0mm	300mm	305g	-5550K	355.00

Parallel Tip

To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. DIN ISO 2380.

\ominus				
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
3.2mm	100mm	25g	-5650K	109.00
3.2mm	150mm	30g	-5660K	162.00
4.0mm	300mm	50g	-5400K	263.00
5.5mm	75mm	55g	-5710K	173.00
5.5mm	100mm	60g	-5720K	178.00
_5.5mm	150mm	65g	-5730K	187.00
5.5mm	200mm	75g	-5740K	219.00
5.5mm	250mm	80g	-5750K	255.00
5.5mm	260mm	81g	-5404K	288.00

TX head screws are used predominantly for engineering and automotive applications. The design of the screw allows high torque levels to be applied without the driver slipping potentially damaging the components.

(③ 🔳		_		
	Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
-	T6	75mm	30g	-5260K	118.00
	T7	75mm	30g	-5262K	118.00
١.	T8	75mm	30g	-5264K	118.00
	T9	75mm	30g	-5266K	114.00
	T10	100mm	60g	-5268K	147.00
	T15	100mm	60g	-5270K	147.00
	T20	100mm	25g	-5272K	147.00
	T25	100mm	85g	-5274K	177.00
	T30	100mm	85g	-5276K	177.00

'Hi-Grip' Pound Thru' Screwdrivers

Through blade screwdriver with chrome vanadium

steel blades and striking heads, suitable for striking with a hammer to free up seized screws. Fully hardened magnetic tips. Comfortable moulded grip. Hexagon blades

DIN ISO 2380/8764.





Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 screwdriver would be suitable for most applications. DIN ISO 8764.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.1	75mm	100g	-3610K	144.00
No.2	100mm	150g	-3620K	196.00
No.3	150mm	220g	-3630K	237.00

Flared Tip

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. Hexagon blades. **DIN ISO 2380.**





Pound Thru' Set



allowing more torque to be applied. Manufactured with hanging hole in the handle for storage. DIN ISO 2380/8764. 6-Piece Set Contents (mm):

Crosspoint: No.1 x 75, No.2 x 100. Flared: 6.3 x 100, 8.0 x 200.

Parallel: 5.0 x 75, 5.0 x 150.





Chrome vanadium steel blades with magnetic tips. Fitted with a unique dual grip triangular handle designed for improved user comfort,

PZ: No.1 x 75, No.2 x 100. **Flared:** 6.3 x 100, 8.0 x 250.

Parallel: 5.0 x 100, 5.0 x 200.

6 **PIECES** 8-Piece Set Contents (mm):

Crosspoint: No.1 x 75, No.2 x 100,

No.3 x 150. **PZ:** No.2 x 100.

Flared: 6.3 x 150, 9.5 x 250. **Parallel:** 5.0 x 100, 5.0 x 200.

8 **PIECES**



Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
6	810g	-5970K	1284.00

8-Piece Set Contents (mm):

Crosspoint: No.1 x 75, No.2 x 100.

PZ: No.2 x 100.

Flared: 6.3 stubby, 6.3 x 100, 8.0 x 200.

Parallel: 5.0 x 75, 5.0 x 150.

8 **PIECES**



Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
8	1010g	-6000K	1645.00

12-Piece Set Contents (mm):

Crosspoint: No.2 x stubby, No.1 x 75,

No.2 x 100, No.3 x 150. PZ: No.2 x 100, No.3 x 150.

Flared: 6.3 x stubby, 6.3 x 150, 8.0 x 200. **Parallel:** 5.0 x 75, 5.0 x 150, 5.0 x 250.





Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
6	925g	-5975K	1419.00

8-Piece Set Contents (mm):

Crosspoint: No.2 x stubby, No.2 x 100. **PZ:** No.1 x 75, No.2 x 100, No.3 x 150, **Flared:** 6.3 x 150, 8.0 x 200.

Parallel: 5.0 x 150.



12



Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
8	1105g	-6010K	1785.00

12-Piece Set Contents (mm):

Crosspoint: No.1 x 75, No.2 x stubby,

No.2 x 100.

Flared: 6.3 x stubby, 6.3 x 100, 6.3 x 150,

8.0 x 200, 9.5 x 250.

Parallel: 5.0 x 75, 5.0 x 100,

5.0 x 200, 5.0 x 250.



Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
12	1581g	-6040K	2590.00



of Pieces each 1280g -5990K 1913.00

12-Piece Set Contents (mm):

Crosspoint: No.2 x stubby, No.2 x 100,

No.3 x 150.

of Pieces

12

PZ: No.1 x 75 No.2 x 100 No.3 x 150. Flared: 6.3 x stubby, 6.3 x 150, 9.5 x 250. Parallel: 5.0 x 100, 5.0 x 200, 5.0 x 250.



KEN-572

-6020K

9-Piece TX Set Contents (mm):
TX: T6 x 75, T7 x 75, T8 x 75,
T9 x 75, T10 x 100, T15 x 100,
T20 x 100, T25 x 100, T30 x 100.

each 1660g

> 9 **PIECES**

2700.00



Page **485**



Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
Q	790d	-eueuk	1901 00

HAND TOOLS



With a traditional 'fluted' design handle. High quality steel blades with satin finish. Magnetic tips, hardened and ground to prolong tool life. This range offers the widest choice of blade selection and blade length. The high impact plastic handles are acid and oil resistant.

A comprehensive selection to meet the demands of modern industry. DIN ISO 2380/8764.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications. DIN ISO 8764.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.0	75	25g	-1000K	88.00
No.1	75	55g	-1010K	118.00
No.2	100	80g	-1020K	139.00
No.3	150	135g	-1030K	201.00
No.4	200	225g	-1040K	308.00
No.1	Stubby	60g	-1210K	118.00
No.2	Stubby	60g	-1220K	118.00

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. DIN ISO 8764.



Flared Tip, Round Blade Same as the parallel tip. DIN ISO 2380.



KENNEDY

Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	Stubby	60g	-3020K	118.00
6.5mm	100	80g	-3040K	139.00
_6.5mm	150	90g	-3060K	149.00
8.0mm	200	155g	-3080K	227.00
10.0mm	250	250g	-3100K	335.00
10.0mm	300	280g	-3120K	361.00

Parallel Tip

HAND TOOLS

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. DIN ISO 2380.

			and the same of	Deliver Lane
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
3.2mm	50	25g	-4520K	101.00
3.2mm	75	25g	-4530K	85.00
3.2mm	100	25g	-4540K	90.00
3.2mm	150	30g	-4560K	101.00
5.5mm	75	55g	-5030K	130.00

Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
5.5mm	100	55g	-5040K	133.00
5.5mm	150	65g	-5060K	134.00
5.5mm	200	70g	-5080K	147.00
5.5mm	250	80g	-5100K	162.00

Flared Tip, Square Blade

Square bladed screwdrivers can be gripped in a spanner or locking wrench to allow greater torque to be applied from the side rather than from directly above the screwdriver.

	N 15U 23	18U.		
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	100	85g	-4040K	126.00
6.5mm	150	95g	-4060K	126.00
8.0mm	200	175g	-4080K	201.00
10.0mm	250	285g	-4100K	236.00

Set Contents (mm):





FLARED 6.5 stubble 6.5 x 100 8.0 x 200 10.0 x 250), 3.2 x), 5.5 x	75, No 150, No 75, No 150. No	0 x 75, .1 stubby, .1 x 75, .2 stubby,
16600 4	1	No No	.2 x 100, .3 x 150, .4 x 200.
	N L		PIECES
Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB

Set Contents (mm):



Weight

1.0kg

KEN-572

-9900K

Price/1 TB

1500.00

Number

of Pieces

11

2275.00

-9920K

1.39kg

'Hi-Grip' Screwdrivers

Designed for maximum grip under load application. The red moulded cushion grip gives optimum operator comfort. Ideal for assembly work. Tough alloy steel blades with satin finish. Magnetic tips, hardened and ground to prolong tool life. DIN ISO 2380/8764.

*Flat blades have hexagon bolster to allow higher torque to be applied via a spanner.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications. DIN ISO 8764.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.0	75mm	35g	-0000K	77.00
No.1	75mm	75g	-0010K	144.00
No.2	100mm	110g	-0020K	185.00
No.3	150mm	170g	-0030K	258.00
No.2	Stubby	65g	-0120K	134.00

TX

TX head screws are used predominantly for engineering and automotive applications. The design of the screw allows high torque levels to be applied without the driver slipping potentially damaging the components.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
T6	75mm	40g	-6060K	125.00
T7	75mm	40g	-6070K	125.00
T8	75mm	40g	-6080K	116.00
T9	75mm	40g	-6090K	116.00
T10	75mm	40g	-6100K	116.00
T15	100mm	80g	-6150K	139.00
T20	100mm	800g	-6200K	139.00
T25	100mm	110g	-6250K	172.00
T30	100mm	110g	-6300K	172.00

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. DIN ISO 8764.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.1	75mm	75g	-0210K	149.00
No.2	100mm	110g	-0220K	191.00
No.3	150mm	170g	-0230K	252.00

Set Contents (mm):

Supplied in clear plastic wallet.

No.1 x 75, No.2 stubby, FLARED POINT No.2 x 100 No.3 x 150.

6.5 stubby, **PIECES** 6.5 x 100, 6.5 x 150 10.0x250.

No.3 x 150.

12

PIECES

Set Contents (mm):

Supplied in clear plastic wallet. 6.5 stubby, No.2 x 100

6.5 x 100, 6.5 x 150, 8.0x200 and 10.0x250. No.1 x 75 No.2 x 100 No.3 x 150. No.1 x 75, No.2 stubby.

Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
8	1.05kg	-9870K	1098.00
12	1.58kg	-0490K	2364.00

Flared Tip, Round Blade


Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. DIN ISO 2380.

\bigoplus				
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	Stubby	65g	-0320K	134.00
6.5mm	100mm	115g	-0340K	216.00
6.5mm	150mm	125g	-0360K	232.00
8.0mm	200mm	195g	-0380K	308.00
10.0mm	250mm	265g	-0400K	402.00

Set Contents (mm):

Supplied in clear plastic wallet.

T6 x 75, T7 x 75, T8 x 75, T9 x 75, T10 x 75, T15 x 100, T20 x 100, T25 x 100, T27 x 100,



Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
11	830g	-6450K	1487.00

Cabinet Screwdrivers

Traditional design cabinet screwdrivers with matt grey high impact plastic handles to ensure a firm yet comfortable grip allowing constant use, giving maximum torque. Chrome alloy steel blades with satin finish. Magnetic tips, hardened and ground to prolong tool life.

DIN ISO 2380/8764.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 screwdriver would be suitable for most applications. DIN ISO 8764.



-7030K

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. DIN ISO 8764.



Flared Tip, Round Blade

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head.

DIN ISO 2380.



\ominus				
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	Stubby	55g	-7320K	79.00


Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
6.5mm	Stubby	55g	-7320K	79.00
5.5mm	75mm	65g	-7330K	79.00
6.5mm	100mm	90g	-7340K	90.00
6.5mm	150mm	105g	-7360K	126.00
8.0mm	200mm	185g	-7380K	193.00
10.0mm	250mm	250g	-7400K	236.00

12-Piece Set Contents (mm):

Supplied in clear plastic wallet.

5.5 x 75, FLARED 6.5 stubby, 6.5 x 100, 6.5 x 150, 8.0 x 200 and 10.0 x 250.

PIECES



No.1 x 75, No.2 x 100 and No.3 x 150.





Page 487

Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
12	1 /15kg	-7490K	1724 00

PIECES



Parallel Tip



Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head.

Size	Weight	Order Code	Price/1
	each	KEN-572	TB
4.8 x 100mm	60g	-7840K	134.00
4.8 x 200mm	75g	-7880K	160.00

Offset Double-Ended Screwdrivers

Designed to give access into otherwise restricted areas. A versatile tool suitable for use in many applications.



Size	Weight each	Order Code KEN-572	Price/1 TB
○ No.1 x → ¾16"	20g	-4210K	116.00
○ No.2 x → ¼"	30g	-4220K	116.00
○ No.3 x → 5/16"	80g	-4230K	116.00
Set - 1 each of above	140g	-4250K	187.00

Mini Screwdriver

Extra light duty screwdriver with magnetic tips. Designed for use on terminals and other electrical work.

N.B. Do not use on live circuits.

		-	
Size	Weight each	Order Code KEN-572	Price/1 TB
○ No.0 x 65	10g	-5190K	52.00
	10g	-5220K	43.00
→ 3.0mm x 100	10g	-5240K	46.00
Set - 1 each of above	35g	-5250K	160.00

YAMOTO Mechanic's Screwdrivers



8.3mm x 200m 572-088

Featuring a classic slimline design favoured by the automotive industry. Black high impact plastic handles. Chrome finish alloy steel blades with satin finish. Magnetic tips, hardened and ground to prolong tool life. Flat blades have hexagon bolster to allow extra torque to be applied using a spanner.

Crosspoint

PZ/Supadriv

Size

No.1

No.2

No.3



TOOLS

HAND



Tip Size	Blade Length	Weight each	Order Code YMT-572	Price/1 TB
No.1	75mm	45g	-0510K	77.00
No.2	100mm	75g	-0520K	101.00
No.3	150mm	130g	-0530K	148.00
No.2	Stubby	50g	-0620K	77.00

Order Code YMT-572

-0710K

-0720K

-0730K

Price/1 TB

89.00

95.00 148.00

Parallel Tip





Tip Size	Blade Length	Weight each	Order Code YMT-572	Price/1 TB
5.5mm	300mm	71g	-0320K	98.00
	250mm	81g	-0340K	129.00
3 Piec	<u>425mm</u>	121g	-0350K	258.00
	e Set	319g	-0400K	411.00

12-Piece Set Contents (mm):

Supplied in clear plastic wallet.

6.3 stubby, 6.3 x 100, 6.3 x 150, 8.3 x 200 and 9.5 x 250.







150mm Flared Tip, Round Blade

Blade

Length

75mm

100mm



Weight

each

45g

85g


150g

Tip Size	Blade Length	Weight each	Order Code YMT-572	Price/1 TB
6.5mm	Stubby	50g	-0820K	65.00
6.5mm	100mm	80g	-0840K	95.00
6.5mm	150mm	90g	-0860K	148.00
8.0mm	200mm	155g	-0880K	196.00
10.0mm	250mm	250g	-0900K	249.00

8-Piece Set

Contents (mm): Supplied in clear plastic wallet.

> 6.3 stubby, 6.3 x 100, 6.3 x 150, 8.3 x 200 and 9.5 x 250.



8 **PIECES**



Number of Pieces	Weight each	Order Code YMT-572	Price/1 TB
8	820g	-0980K	918.00



PIECES

Screwdriver

12

PIECES

Combined & Fluted Handle Screwdriver Set

Seven 'volt-tested' screwdrivers plus five noninsulated engineer's and electrician's screwdrivers.

Supplied in clear plastic wallet.

12-Piece Set Contents (mm): Non-Insulated

6.3 stubby. FLARED 4.8 x 75,

4.8 x 150 and PARALLEL 4.8 x 250. **Volt-Tested**

2.5 x 85, 4.0 x 100, 5.5 x 125 and 6.5 x 150.

No.2 x $\frac{1}{4}$ " slotted offset. No.0 x 75, No.1 x 100, No.2 x 100.

Number Weight of Pieces each 745g

YAMOTO

identification on the end

5 x 150.

6 x 150,

8 x 200.

Weight

each

715g

for easy location.

6-Piece Set Contents (mm): No. 1 x 75 No. 2 x 100.

6

PIECES

Number

of Pieces

6

8-Piece Set

Contents (mm):

No.1 x 75

No.2 x 100.

No.2 x 100.

3 x 75, 5 x 150.

6 x 150,

8 x 200,

6 x stubby.

Ergonomically designed handles

Tri-Line™

which are dual material and three-sided for

improved torque and reduced fatigue. Chrome vanadium steel blades with magnetic tips and a hanging hole in handle. The handles have

Order Code Price/1 KEN-572 TB -5920K 1361.00

Screwdriver

VATOR Screwdriver Sets

Chrome vanadium steel blades with magnetic tips. Acrylic handles.

8-Piece Set Contents (mm):

6 stubby, 3 x 100 and 8 x 200.

3.2 x 75 and PARALLEL 4 x 150.

No.2 stubby, No.1 x 75 and

No.2 x 100.

ACRYLIC GRIP HANDLES

8 **PIECES**


Price/1 Number Weight Order Code SEN-572 TB of Pieces each 8 690g -9980K 499.00

12-Piece Set Contents (mm):

6 stubby, 6 x 100, 6 x 150, PARALLEL 8 x 200 and 9.5 x 250.

No.2 stubby, No.1 x 75,

No.2 x 100 and No.3 x 150. 3.2 x 75. 4 x 150 and



PIECES

Number Weight of Pieces each 12 1.25kg

Price/1 Order Code SEN-572 -9990K 1473.00

8-Piece Set

6.3 stubby, 6.3 x 100 and 8.0 x 200.

4.0 x 100.

No.1 x 75. and No.2 x 100.

ACRYLIC GRIP HANDLES

each

580g

8 **PIECES**



Price/1 Order Code SEN-572 -9890K 625.00

Dual Grip Screwdriver Sets

Comfort rubber grip handles with chrome vanadium, chrome-plated blades and

5-Piece Set Contents (mm):

magnetic tips.

 $^{\oplus}$ No.2 x 100, No.3 x 150.

3 x 75 PARALLEL 5 x 150.


8 x 200.

PIECES

Number Weight Price/1 Order Code SEN-572 TB of Pieces each 5 600g -9050K 345.00

RUBBER

GRIP **HANDLES**



3 x 75, 5 x 150, PARALLEL 5 x 250.

8 x 200, 6 stubby.

ACRYLIC

GRIP

RUBBER GRIP HANDLES

10 **PIECES**

(

Number Weight of Pieces each

No.2 x

stubby.

3 x 75

5 x 250.

6 x 150, 8 x 200,

9.5 x 300, 6 x stubby.

RUBBER

GRIP

HANDLES

PARALLEL 5 x 200, 5 x 150

No.1 x 75

No.2 x 100,

No.3 x 150.

995g

15-Piece Set Contents (mm):

SEN-572

-9100K 725.00

Contents (mm):

3.0 x 75 and

No.2 stubby,

Number Weight

15 **PIECES** Number

of Pieces

Weight each SEN-572 1.63kg -9150K

Price/1 No.1 x 75, No.2 x 100, No.3 x 150,

HAND TOOLS

PIECES Number of Pieces 8

8

Weight each 875g

YMT-572

Order Code

YMT-572

-2060K

-2080K

Price/1

Price/1

TB

586.00

717.00

PRODUCTS ARE ONLY AVAILABLE VIA YOUR DISTRIBUTOR

of Pieces

Price/1

999.00

🔽 Insulated Interchangeable Screwdriver Set

Ergonomic insulated full size handle, swivel cap and eight interchangeable drivers supplied in a compact protective pouch with belt loop. 2-in-1 design, use the detachable swivel cap for fast (low torque) driving, or use the full size detachable ergonomic handle for higher torque

PIECES

Safe up to 1000V AC/1500V DC.



10 Piece Set Contents (mm):

0.4 x 2.5 x 100, 0.5 x 3.0 x 100, 0.8 x 4.0 x 100, 1.0 x 5.5 x 100 and 1.2 x 6.5 x 100.

No.0 x 100, No.1 x 100 and No.2 x 100.





Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
10	365g	-5870K	2014.00

1000V Dual Grip VDE Screwdrivers

A fully insulated screwdriver VDE tested up to 1000V. Professional high grip handles, magnetic tips,

chrome vanadium steel blades.



Crosspoint

TOOLS

HAND

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.0	60mm	20g	-7900K	322.00
No.1	80mm	60g	-7910K	375.00
No.2	100mm	90g	-7920K	448.00

Parallel Tip

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head.

Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
2.5mm	75mm	20g	-7940K	322.00
4.0mm	100mm	60g	-7950K	375.00
5.5mm	125mm	75g	-7960K	480.00
6.5mm	150mm	110g	-7970K	521.00

Set Contents (mm):

2.5 x 75, 4.0 x 100, 5.5 x 125, PARALLEL 6.5 x 150.

No.0 x 60, No.1 x 80, No.2 x 100.



Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
7	715g	-8000K	1586 00

Electrician's VDE Square Section Handle Screwdrivers

Volt-tested to ensure safety on or near electrical equipment up to 1000V AC or 1500V DC. Insulated blades with magnetic tips. Conform with DIN 7438 and DIN EN 60900.



Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications.





Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
No.0	75mm	27g	-5820K	99.00
No.1	100mm	50g	-5830K	118.00
No.2	100mm	80g	-5840K	136.00

Parallel Tip

6.5mm

Slotted head screws are the most commonly used screw. The tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping.



80g

100g

125mm

150mm

Set Contents (mm): Supplied in clear

plastic wallet.

2.5 x 85 4.0 x 100, 5.5 x 125, PARALLEL 6.5 x 150.

No.0 x 75, No.1 x 100, No.2 x 100.

PIECES

Number of Pieces	Weight each
7	495¢



Price/1 KEN-572 -5900K 954.00

164.00

171.00

-5790K

-5800K

Spiral Ratchet Screwdrivers

Polished chrome plated body. 3-way ratchet. Quick release chuck. ABS plastic/lacquered wood handles - 440 mm has fluted handle for extra grip. Chrome vanadium steel bits. Supplied with crosspoint and flared screwdriver bits.




Ditc Sizos

				Dita Sizes	KEN-572
			D: //	5.5mm Flat	-8820K
	Size	Order Code	Price/1	7.0mm Flat	-8840K
_		KEN-572	ТВ	No.1 Crosspoint	-8860K
	430mm	-8160K	773.00	No.2 Crosspoint	-8880K

Ratchet Screwdriver

Flared blade. Three-position high performance ratchet. Suitable for rapid tightening or loosening of fastenings in a single action.



Precision Jeweller's Screwdriver Set

12-in-1 Set

This handy jeweller's screwdriver set has six interchangeable $30 \times 3.6 \text{mm}$ hex. Double ended bits.

Contents: 1.00, 1.50, 2.00, 2.50, 3.00, 3.50, T20, PH000,

PH00, PH0, PH1, PZ0

Handle size:

90 x 7.7mm diameter.



Order Code

Price/1

TB 129.00 129.00

129.00

129.00

Number of Pieces	Order Code KEN-572	Price/1 TB
7	-9000K	438.00

KENNEDY Aluminium-Bronze PROFESSIONAL Spark-Resistant Screwdrivers

Spark-resistant tools are used to eliminate the chances of accidental fires or explosions in potentially combustible or explosive environments. They resist the sparks that a standard tool could potentially create when striking hard surfaces. The use of spark resistant tools is essential in many industrial applications such as petroleum and chemical manufacturing, spray booth operations, the marine industry, the mining industry, the paper industries, or any location where flammable vapours or combustible residues are present. Aluminium-bronze spark-resistant safety tools are manufactured to 25HRC and offer a breaking strain of 75 - 85kgf/mm².



Spark-resistant tools must be maintained with special care. Frequent cleaning/re-dressing to remove ferrous particles or contaminants, which may impair the spark resistant properties, is essential.

Blade			
Diauc	Weight	Order Code	Price/1
Length	each	KEN-575	TB
100	60g	-4020K	1003.00
150		-4040K	1405.00
200		-4060K	1706.00
250		-4080K	2308.00
300	200g	-4100K	2810.00
			TW
	100 150 200 250	100 60g 150 80g 200 120g 250 180g	100 60g -4020K 150 80g -4040K 200 120g -4060K 250 180g -4080K

(4)			KENNIE	DY 275-656
Tip	Blade	Weight	Order Code	Price/1
Size	Length	each	KEN-575	TB
No.1	75	55g	-4520K	803.00
No.2	100	60g	-4540K	1003.00
No.3	150	100g	-4560K	1405.00
No.4	200	120g	-4580K	1706.00

SCREWDRIVERS

s 572

Yankee Screwdriver Bits

Manufactured from high quality chrome vanadium steel. To suit Yankee spiral ratchet screwdrivers.

Light Duty

To suit Kennedy 300mm Yankee and Stanley® 135B™ Yankee, Handyman 133B Yankee and Handyman 233B Yankee.



Medium Duty

To suit Kennedy 440mm Yankee and Stanley® $130B^{TM}$ Yankee.



Heavy Duty


To suit Kennedy 620mm Yankee and Stanley® 131B™ Yankee.



Precision Screwdrivers

Nickel chrome molybdenum steel blades, hardened and tempered in choice of crosspoint and parallel tips. Chrome plated, with swivel tops which resist oil and acid. Supplied in plastic cases. Ideal for jewellers and watchmakers.

Parallel



Crosspoint

Туре	Tip Size (mm)		Order Code KEN-572	Price/1 TB
	PHO-4	5g	-9200K	47.00
3	РН0-з	10g	-9210K	47.00
CROSSPOINT	PH0-2	10g	-9220K	47.00
	PH0	15g	-9230K	47.00
	PH1 ₋₁	30g	-9250K	47.00

🛾 Jeweller's & Watchmaker's Tool Sets Carbon Steel & Alloy Steel Blades



ALLOY STEEL BLADES

A quality range of precision screwdrivers. Combination tool and driver sets have carbon steel blades (tweezers are stainless steel). Driver only sets have nickel chrome molybdenum alloy steel blades. All with attractive chromed handles.

11-Piece Set **Contents:**

1.0, 1.2, 1.4, 1.8, 2.4 and 3.0mm. PARALLEL



CARBON STEEL BLADES

CARBON STEEL BLADES

PIECES

11

PIECES

PHO-2, PHO and PH1 Fine point awl and tweezers.





Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
11	220g	-9040K	416.00

11-Piece Set Contents:

HAND TOOLS

1.0, 1.2, 1.4, 1.8, 2.4








Number Weight of Pieces each		Order Code KEN-572	Price/1 TB
11	210g	-9050K	416.00

11-Piece Set **Contents:**

1.0, 1.2, 1.4, 1.8, 2.4 and 3.0mm.




PHO-2, PHO and PH1, fine point, awl and magnet.



Number Weight of Pieces each		Order Code KEN-572	Price/1 TB	
11	225g	-9060K	416.00	

6-Piece Parallel Set **Contents:**

1.0, 1.4, 2.0, 2.4, 3.0 and 3.8mm.



Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
6	155g	-9070K	175.00

6-Piece Crosspoint Set Contents:

PHO-4, PHO-3, PHO-2, PHO, PH1-2 and PH1.

a **PIECES**



ALLOY STEEL BLADES

ALLOY STEEL BLADES

6	- 18
PIECES	de


Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB	
6	140g	-9080K	175.00	

6-Piece Parallel & **Crosspoint Set** Contents:

1.4, 2.0, 2.4, and PARALLEL 3.0mm.



PHO and PH1.



6	
PIECES	

Number of Pieces	Weight each	Order Code KEN-572	Price/1 TB
6	155g	-9090K	175.00

5-Piece Hexagon **ALLOY STEEL BLADES Key Driver Set**

Contents: 0.9, 1.3, ① 1.5, HEXAGON and 1.5,2.0 2.5mm.



Number Weight of Pieces each		Order Code KEN-572	Price/1 TB	
5	130g	-9886K	235.00	

5-Piece Hexagon **Ball Key Driver Set Contents:**

1.3, 1.5, 2.0, 2.5 HEXAGON and BALL 3.0mm.



ALLOY STEEL BLADES

Number Weight of Pieces each		Order Code KEN-572	Price/1 TB
5	130g	-9887K	299.00

5-Piece Nut Driver Set **Contents:**

3.0, 3.5 4.0, 4.5 HEXAGON and 5.0mm.

PIECES



5	
PIECES	

Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
5	170g	-9888K	299.00




Expert quality, hardened and tempered chrome alloy steel blades. Fitted with a unique dual grip handle with revolving top designed for added user comfort whilst allowing more torque to be applied.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications.





Parallel Tip

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head.

\longmapsto				
\smile				
Tip	Blade	Weight	Order Code	Price/1
Size	Length	each	KEN-572	TB
1.4mm	40	15g	-4300K	126.00
2.0mm	40	15g	-4310K	126.00
2.4mm	40	15g	-4320K	126.00
3.0mm	40	15g	-4330K	126.00
2.4mm	75	15g	-4340K	126.00
3.0mm	75	20g	-4350K	126.00
4.0mm	100	25g	-4360K	144.00


TX head screws are used predominantly for engineering and automotive applications. The design of the screw allows high torque levels to be applied without the driver slipping.

		-		
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 TB
T6	40	15g	-6470K	107.00
T8	40	15g	-6472K	107.00
T9	50	15g	-6474K	107.00
T10	50	15g	-6476K	107.00
T15	60	20g	-6478K	107.00
T20	60	20g	-6480K	107.00

Set

Alloy steel blades, black oxidised tips, dual material handles for improved grip, revolving end caps. Supplied in leatherette zip around case.

Set Contents:







Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
6	170g	-6490K	753.00

Set

All screwdrivers have 40mm blade length. Complete with protective zip case.

Set Contents:

1.4, 2.0, 2.4 PARALLEL and 3.0mm.



PH0-3, PH0-2 and PH-0.





Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
7	165g	-4450K	834.00

Set

6

PIECES

Complete with protective zip case.

Set Contents:

1.4 x 40, 2.0 x 40, 2.4 x 75, 3.0 x 75 and 4.0 x 100mm.



PH0-3 x 40, PH0-2 x 75, PH-0 x 75 and PH1 x 100mm.





Number of Pieces	Weight	Order Code	Price/1
	each	KEN-572	TB
9	265g	-4470K	1131.00



HAND TOOLS