

SITESAFE



Leak Detector Spray

LDA500

For checking for the most minute leaks in any gas or air pressurised systems including commercial vehicle air brakes and pressure vessels. Contains no alcohols or solvents, is not caustic and contains a rust inhibitor. Spray directly onto the suspect area using the extension tube and examine for bubbling which will indicate leakage.



Size	Order Code	Price/1 TB
500ml	-3340K	314.00

De-ionised Water

DW25

For use in lead-acid car batteries. Also suitable for domestic appliances such as steam irons and steam cleaners, avoids problems caused by scaling. Can be used as a final rinse in car washing to avoid 'spotting'. Also suitable for rinsing scientific glassware.



Size	Order Code	Price/1 TB
25ltr	-4250K	1025.00

SOLENT
MAINTENANCE

Leak Detector Spray

SL1-400A

A specially formulated, performance white fluid, designed to identify even the smallest gaseous leak. Applies a thin uniform film of surface active agents which identifies any leak or bleeding of joints. Bubbles in the film indicate the location of the leak. Will not give a false reading if mechanical sensing equipment is used. Suitable for use with most common gases.



Size	Order Code	Price/1 TB
400ml	-0340K	468.00

Fault Detector Freeze Spray

NEW

SFC-415F

Fault Detector Freezer spray is a very cold rapidly evaporating high pressure gas jet. Applying to electronic components will lower the temperature of the component. Any faulty overheating component will cool and return to correct operation, thus indicating the faulty component. Cools objects very rapidly down to temperatures of -50°C. Can also be used to shrink fit metal parts where the application of heat would be inappropriate and can be used to freeze chewing gum deposits to aid removal.

Size: 415ml



Size	Order Code	Price/1 TB
415ml	-9580K	599.00

3-Part Flaw Detector Inspection System

Fast reliable method for visually inspecting and spot-checking surfaces of welds, exotic alloys or standard metals, highly stressed structural members, critical castings, shafts, gears, spindles, and any other hard part where identification of surface flaws is essential. Detects flaws such as cracks, pin holes, welding laps and porosity either during manufacture or on-site.



Flaw Detector Cleaner Spray

SF1-500B

Quick drying, powerful solvent for cleaning surfaces prior to testing. Removes contaminants including oils, greases and grime.

Size	Order Code	Price/1 TB
500ml	-0240K	889.00

Flaw Detector Dye Penetrant

SF2-500B

Highly sensitive red dye, for use when detecting flaws on metal components under normal lighting conditions.

Size	Order Code	Price/1 TB
500ml	-0260K	889.00

Flaw Detector Developer

SF3-500B

White film to highlight any faults which have been detected when using Flaw Detector Penetrant. The product should be removed using Flaw Detector Cleaner Spray once cracks have been found and marked.

Size	Order Code	Price/1 TB
500ml	-0280K	889.00

Water Based Anti-Spatter Fluid

SW2-400C

No solvent or silicone content. Fine spray pattern gives good coverage, prevents spatter build-up on jigs, work. Ideal where further process work is involved, eg painting, galvanising with a rust inhibitor.



NEW

Size	Order Code	Price/1 TB
500ml	-9740K	670.00

Welder's Anti-Spatter Spray

SW1-400C

Solvent-based coating applied to metal before welding to prevent spatter from sticking to the metal. CO₂ propelled aerosol. Non-flammable. Silicone-free and removable with solvents prior to galvanising or painting.



Size	Order Code	Price/1 TB
400g	-0840K	325.00

Welder's Anti-Spatter Fluid

Reduces the risk of joint puddling and greatly reduces preparation time prior to final painting. Does not affect any subsequent galvanising or painting operations. Evaporates under normal weld temperatures. Dichloromethane and silicone-free. Non-flammable, non-toxic, non-corrosive and bio-degradable.



Size	Order Code	Price/1 TB
5ltr	-9300K	592.00
20ltr	-9310K	1777.00