## Maintenance Liquid

#### AC-90

Displaces water, helps start damp engines, penetrates rust, protects from corrosion, lubricates and stops squeaks. Silicone free, electrically nonconductive and can be used on or near electrical components, motor circuits etc, without affecting insulation or causing short circuits. Available in aerosols that use no CFCs and are ozone friendly or in screw top metal cans.

**Does Not Contain** Kerosene\* Paraffin\* or Naphtha\*. (\*These products are used by some other maintenance sprays or water displacing sprays but are associated with skin drying and irritations.)

NEW



Size	Order Code ACN-732	Price/1 TB
250ml Aerosol	-0050K	150.00
425ml Aerosol	-0150K	265.00
5ltr Can	-0200K	1499.00
Applicator	-0500K	199.00

# SHERWOOD SHALTY CUTTING TOOLS

# **STD Tapping & Drilling** Non-Soluble Foam Lubricant

Foam aerosol penetrates and is able to cling to normally inaccessible areas and moving cutting edges. Can be used on yellow metals without the risk of staining.



Size	Order Code SHR-732	Price/1 TB
400ml	-4210K	567.00

# SOLENT.

# Maintenance Spray

SM4-500C 'M4 Plus'

Lubricates: High performance mineral oil based lubricant with

### Displaces Water:

Helps start damp engines.

#### Penetrates:

Releases rusty fixings.

Cleans & Protects: Cleans metal surfaces and prevents rusting of treated parts. Does not contain naphtha, kerosene or paraffin

which are all associated with operator skin dryness, cracking or dermatitis. CO<sub>2</sub> non-flammable propellant. Does not contain silicone. Electrically nonconductive at normal ranges found in the home. Care must be taken if used on some electrical plastic components where 'crazing' may occur.



Size	Order Code <b>SOL-732</b>	Price/1 TB
500ml	-0460K	297.00

# Sherwood STD

# Fluid Spray

Non-soluble tapping and drilling aerosol spray that penetrates and clings to normally inaccessible areas and moving cutting edges.



Size	Order Code SHR-732	Price/1 TB
400ml	-4000K	562.00

# Multi-Purpose Oil Spray CO<sub>2</sub>

### SM3-500C

Multi-purpose mineral lubricating oil formulated to have a wide operating range. It lubricates, penetrates, cleans and protects. Use on locks and hinges. Cleans and protects tools. Helps to release stubborn and rusted bolts. Outdoor protection making it ideal for boats. Suitable for household use yet strong enough for industrial applications. Contains a special blend of anti-rust agents which will

protect all treated surfaces against corrosion. Does not contain silicone or CFCs.



Size	Order Code SOL-732	Price/1 TB
500ml	-0450K	464.00

#### **Sherwood STD Liquid** (Poly Bottle)

Low odour liquid. Coats the cutting edge with a film of EP additives.

### **Sherwood STD Compound**

Low melting point paste maintains a continual lubricant feed to the cutting edge. Hand applied. Suitable for the most severe cutting operations.



#### Order Code SHR-732 -4020K 652.00 500ml -4060K 5627.00 500g -4040K 534.00

## **Dry Moly Spray** SD1-500B

Premium grade dry molybdenum particle lubricant. Fast drying. Ideal for fastener lubrication. Effective on all grades of steel, copper, brass, stainless steel and foundry equipment where high temperatures are common. Also for open gear lubrication and any location where a wet coating is not acceptable or would burn off. Works at up to load rates of 100.000psi. No silicone content.



Size	Order Code <b>SOL-732</b>	Price/1 TB
500ml	-0200K	979.00

# KENNEDY.

### Air Tool Oil

Excellent air release quality, low foaming ability and resists clogging. Contains anti-rust and anti-wear additives. Extremely resistant to water absorption and can be mixed with all mineral oil based lubricants without draining the system. Can be used on air tools. ISO Grade VG22.



Size	Order Code KEN-732	Price/1 TB
500ml	-8000K	366.00
5ltr	-8050K	2575.00